



Date of Publication: April 23, 2010

### Technical Data Sheet: ACAS

Item Number: ACAS

Item Name: Polyolefin Temporary Antistatic Concentrate

Let Down Resin: PE or PP

Regulatory Status:  Heavy Metal Free  CONEG  
 RoHS  WEE Compliant  
 Not Radioactive  FDA – Indirect Food Contact\*  
 No REACH Substances of Very High Concern

Processing Range 200°C - 240 °C Do not exceed 260°C  
Melting Point 110°C

Let Down Ratio: \*As required\*

**Guidelines for use:**

Begin adding ACAS at a usage rate of 2% and increase usage until reaching the desired antistatic performance. Increased additive amounts will also begin to increase the gloss of the final application. After the usage rate has been determined, final application testing is recommended to ensure part performance is in accordance with all applicable specifications.

\*Call UCC for details on FDA limitations of use.

**Disclaimer:** The data contained in this report is being provided by Uniform Color Company ("UCC") as a complimentary service, and as such, is being provided without warranty (express or implied) or representation as to its accuracy or completeness. Moreover, this report is intended only for the internal use of the recipient, and shall not be disclosed to any third party, nor reproduced or distributed by the recipient, without UCC's prior written consent. The end user is solely responsible for the physical property requirements of their end application. UCC recommends that the end user performs all relevant physical testing to ensure no adverse results from the use of this product are experienced.

942 Brooks Avenue Holland MI 49423

(616) 394.3800 · (800) 44.COLOR

Fax: (616) 394.3824

[uniformcolor.com](http://uniformcolor.com)